



OF Bearing Industrial Co.,Ltd.

KOYO K24X30X17H needle roller bearings



Bearing No. K24X30X17H

K24X30X17H Bearing 2D drawings and 3D CAD models

Bore Diameter	24 mm
Outer Diameter	30 mm
Fw	24 mm
Ew	30 mm
Bc	17 mm
Weight	0.020 Kg
Basic dynamic load rating (C)	19.8 kN
Basic static load rating (C0)	27.7 kN
(Grease) Lubrication Speed	12000 r/min
(Oil) Lubrication Speed	19000 r/min
Category	Needle Non Thrust Roller Bearings
Inventory	0.0
Manufacturer Name	KOYO
Minimum Buy Quantity	N/A
Weight / Kilogram	0.015
EAN	0060579020447
Product Group	B04144
Rolling Element	Needle Roller Bearing
Component	Roller Assembly Only
Enclosure	Not Applicable
Self Aligning	No
Retainer	Yes
Number of Rows of Rollers	Single Row
Separable	No
Closed End	Not Applicable



OF Bearing Industrial Co.,Ltd.

Inch - Metric	Metric
Thrust Bearing	No
Long Description	24MM Bore; 30MM Outside Diameter; 17MM Width; Needle Roller Bearing; Roller Assembly Only; No Self Aligning; Retainer; Single Row of Rollers; No Separable
Other Features	Radial Roller Hardened Steel Cage
Category	Needle Non Thrust Roller Bearing
UNSPSC	31171512
Harmonized Tariff Code	8482.40.00.00
Noun	Bearing
Keyword String	Needle
Manufacturer URL	http://www.koyousa.com
Manufacturer Item Number	K24X30X17H
Weight / LBS	0.044
Bore	0.945 Inch 24 Millimeter
Outside Diameter	1.181 Inch 30 Millimeter
Width	0.669 Inch 17 Millimeter
Bearing No.	K24X30X17H
Cr	19.8
C0r	27.7
Cu	4.35
Grease lub.	12000
Oil lub.	19000
P/S	S
(Refer.) Mass(kg)	0.020
Shaft(max.)	24.000
Shaft(min.)	23.991
Housing(max.)	30.020
Housing(min.)	30.007



OF Bearing Industrial Co.,Ltd.